

Congratulations and thanks for your purchase! We have tried to make the assembly instructions as clear and concise as possible so you can get on with enjoying your tent quickly and with minimal fuss.

We've also included some tips on how to prolong the life of your tent – if you follow this advice, you will be able to enjoy your tent for years to come!

**Contents:**

- 1 rain fly
- 2 inner tent
- 6 fiberglass poles
- 8 steel poles
- 8 black pole joints
- 50 tent stakes
- 24 guy ropes
- 1 repair kit

**Tent Assembly Instructions, Model: Hulk**

**Poles and components:**

- Steel poles: extend all sets of steel poles and line them up on the ground
- Fiberglass poles: extend all sets of fiberglass poles and line them up on the
- 

**Rain fly:**

- Lay the fly on the ground as flat as possible
- Insert each color coded tent pole into the corresponding color coded pole sleeve
- Insert the black plastic elbow to the ends of each fiberglass tent pole
- Clip the extended steel poles to each corner of the rain fly with the pre-bent end at the top where you then connect the fiberglass poles
- Insert the top ends of the assembled steel poles into the free end of the adjacent black plastic elbow that you connected to the fiberglass poles
- Secure all steel poles to the bottom of the rain fly using the pins found along the bottom edge of the rain fly
- Insert the smallest tent pole through the pole sleeve located on the door awning – insert each end into the adjacent PP webbing pocket – the awning should stand out from the rain fly taught
- Ensure that the guy ropes are secure to the guy rope tabs on the rain fly and stake the opposite ends of the guy ropes into the ground – adjust the tension of the guy ropes by sliding the tension adjusters along the guy ropes until they are taught.
- You can now use the rain fly as a free standing shelter

**Inner tents:**

- Take an inner tent inside the assembled rain fly to its appropriate location
- Starting from the rear of the inner tent, stake down the corners along the bottom edge of the rain fly
- Hook the inner tent to the underside of the rain fly starting from the bottom rear and work your way forward to the top using the toggles on the outer wall of the inner tent and loops running along the underside of the rain fly
- Repeat the above steps for the rest of the inner tents – you can leave some of the inner tents out to increase the living or storage capacity and to reduce the travel weight of the whole tent.

**Caring for your tent:**

1. Keep it clean: Don't set up your tent in the mud, avoid putting muddy clothing and gear in the sleeping compartments as sand and dirt can scratch the water proof coating and damage zippers
2. UV light can accelerate fabric degradation. Therefore, set up your tent in the shade when possible and use the rain fly to protect the inner tent
3. To prolong the life of your tent floor, use a separate sheet of PE fabric underneath the tent to protect against abrasion
4. When packing up, shake out dirt and sand as much as possible
5. At home, clean your tent with a damp cloth, never use harsh cleaning chemicals, and air dry

Visit us online at [www.campingequipmentco.com](http://www.campingequipmentco.com) and be sure to join our Facebook and Twitter pages for new product information and to receive special offers and discounts on our camping equipment.



www.campingequipmentco.com  
Tent Assembly Instructions  
HULK

6. When storing, allow the tent to sit loosely to prevent creases

Visit us online at [www.campingequipmentco.com](http://www.campingequipmentco.com) and be sure to join our Facebook and Twitter pages for new product information and to receive special offers and discounts on our camping equipment.